



CaviBlaster 1228-G

Gasoline Engine, 12 gpm & 2,800 psi

Specifications and Options

Our most popular commercial unit, is a compact and lightweight system with superior cleaning performance utilizing the Ultra-Cavitation technology

Accessories Included:

Feed Hose (15 feet) with electric suction pump, By-Pass Hose (15 feet), High Pressure Hose (50 feet), Zero-Thrust Balanced Gun, Battery Start

Optional Accessories:

Additional pressure hose available in 50 ft or 100 ft sections

Max. Pressure hose length recommended up to 300 ft (100 meters) total



SKID Dimensions

Length w/o handle	35" / 89 cm
Length w handle	45" / 114 cm
Width	26" / 66 cm
Height	29" / 74 cm
Weight	230 Lbs / 105 Kg

Pump System

Pressure Pump	General TSF 2421 Plus
Pump Material / Type	Triplex Plunger - Brass
Flow Rate	12 gpm / 45 Lpm
Pressure	2,800 psi / 193 Bar
Hose Diam/Max Lgth	1/2" - 300 ft / 100 meters

Shipping Dimensions

Pallet 40x48x36"	330 Lbs Gross weight
------------------	----------------------

* Pricing and specifications subject to change without notice

Ideal For

Small to Mid size Boat Hulls
Piers, Pilings & Seawalls
Running gear & Out drivers
Pools & Indoor Underwater Instalations

Feed System

Feed Pump	Johnson L2200
Pump Material	Thermoplastic 12 V Subm.
Flow Rate @ Max Lift	16gpm/60Lpm@12Lft/3.6m

Tool Options

Zero-Thrust Balanced Gun
Double Un-Balanced Guns
Single CaviDome
ROV Lance

CaviDyne LLC, 5077 Fruitville Rd. Suite - 109-157, Sarasota FL, 34232 USA

Phone: (352)275-5319, sales@cavidyne.com, www.cavidyne.com



CAVIBLASTER™