

CaviBlaster 1625-D

Diesel Engine, 16 gpm & 2,500 psi

Specifications and Options

This unit replaces the popular 1620 diesel model, the increased flow generates a higher level of cavitation, for faster and more efficient cleaning

Accessories Included:

Feed Hose (15 feet), By-Pass Hose (15 feet),
High Pressure Hose (50 feet), Zero-Thrust Balanced Gun, Battery Start

Optional Accessories:

Additional pressure hose available in 50 ft or 100 ft sections
Max. Pressure hose length recommended up to 300 ft (100 meters) total



SKID Dimensions

Length w handle	49" / 124 cm
Width	31" / 79 cm
Height	56" / 142 cm
Weight	600 Lbs / 273 kg
Fuel Containment Pan	YES
Lifting Eyes	YES

Pump System

Pressure Pump	Udor NX 75/150
Pump Material / Type	Brass / Positive Displacement
Flow Rate	16 gpm / 60 Lpm
Nozzle Pressure	2,500 psi / 172 bar
Hose Diam/Max Lgth	3/4" - 300 ft @ 19 mm /100 m

Shipping Dimensions

Pallet 40x48x60"	700 Lbs Gross weight
------------------	----------------------

Drive System

Engine	Kubota D1105-E3B
EPA Regulation	USATier-4 / EUStage III-A
Engine Type	3 Cylinder / 4-Cycle
Cooling System	Liquid w/Axial fan
Combustion System	IDI Naturally Asp.
Exhaust	CycloneMfr / Spk arrester
Int. Output	32.9 HP / 24.5 kW
Transmission	Belt Drive
Starting System	Electric Starter
Emergency Shut-off	YES

Feed System

Feed Pump	Johnson L2200
Pump Material	SS Shaft
Flow Rate @ Max Lift	20gpm/76Lpm @10Lft/3m
Drive	12V / 7.5 Amp Electric

Tool Options

Zero-Thrust Balanced Gun
Double UnBalanced Guns
Single CaviDome
ROV Lance

* Pricing and specifications subject to change without notice

CaviDyne LLC, 5077 Fruitville Rd. Suite - 109-157, Sarasota FL, 34232 USA

Phone: (352)275-5319, sales@cavidyne.com, www.cavidyne.com



CAVIBLASTER™