

CaviBlaster 2022-E50/E60

Electric Motor, 20 gpm & 2,200 psi

Specifications and Options

This is our largest commercial unit, operating at lower pressures it's designed specifically not to damage paints or coatings yet strong enough to clean to bare metal if needed

Accessories Included:

Feed Hose (15 feet), By-Pass Hose (15 feet),
High Pressure Hose (50 feet), Zero-Thrust Balanced Gun

Optional Accessories:

Additional pressure hose available in 50 ft or 100 ft sections
Max. Pressure hose length recommended up to 300 ft (100 meters) total



SKID Dimensions	
Length	48" / 122 cm
Width	34" / 86 cm
Height	36" / 91 cm
Weight	900 Lbs / 409 kg
Lifting Eyes / FL Slots	YES / YES

Pump System	
Pressure Pump	Udor Penta-D 70/280
Pump Material / Type	Brass / Triplex Plunger
Flow Rate	20 gpm / 76 Lpm
Nozzle Pressure	2,200 psi / 152 Bar
Hose Diam/Max Lgth	3/4" - 600 ft / 200 m

Shipping Dimensions	
Pallet 40x48x44"	1,000 Lbs Gross weight

Feed System	
Feed Pump	Self-Priming Centrifugal
Pump Material	Brass
Driver	Electric Motor
Flow Rate	62 GPM / 235 L/m
Max Lift	20 ft / 6 meter

Tool Options	
Zero-Thrust Balanced Gun	
Double Zero-Thrust Balanced Guns	
Single CaviDome	
ROV Lance	

Drive System	
Driver	Electric Motor
Enclosure	TEFC
Frame	264T
Hertz	60
Voltage	208-230/460
Phase	3
Output HP/kW	40 / 29.9
Speed RPM	1750
Transmission	Direct Drive
Starting System	Soft Start
Control Box	S.S. NEMA 4X / IP56

* Pricing and specifications subject to change without notice

CaviDyne LLC, 5077 Fruitville Rd. Suite - 109-157, Sarasota FL, 34232 USA

Phone: (352)275-5319, sales@cavidyne.com, www.cavidyne.com



CAVIBLASTER™