



CaviBlaster 2040-ROV

Remote Operated Vehicle, 20 gpm & 4,000 psi

Specifications and Options

A compact and powerful submersible hydraulically driven cleaning system compatible with a wide range of ROVs available with different types of lances

Accessories Included:

Full forward thrust lance or balanced zero thrust lance

Optional Accessories:



SKID Dimensions	
Length	24" / 60 cm
Width	36" / 91 cm
Height	48" / 121 cm
Weight	350 Lbs / 160 kg

Pump System	
Pressure Pump	CAT 3560
Pump Material / Type	SS/Brass - Positive Disp.
Flow Rate	20 gpm / 76 Lpm
Nozzle Pressure	4,000 psi / 275 Bar
Hose Diameter	3/4"

Drive System	
Drive System	Direct Drive
Manufacturer / Model	Cross, Alum.Body
Motor	Hydraulic Rotary Vane
Seize cu. Inches	6.15CIR
Hyd. Flow Pressure	33gpm/122Lpm-3,000psi/160Bar

Ideal For
Deep water operations
Piers, Pilings & Seawalls
Running gear & Out drivers

Tools	
Tool Type	Lance

Shipping Dimensions	
Pallet 48x24x50"	400 Lbs Gross weight

* Pricing and specifications subject to change without notice

CaviDyne LLC, 5077 Fruitville Rd. Suite - 109-157, Sarasota FL, 34232 USA

Phone: (352)275-5319, sales@cavidyne.com, www.cavidyne.com



CAVIBLASTER™