



## CaviBlaster 3040-E50/E60

Electric Motor, 30 gpm & 4,000 psi

### Specifications and Options

This is an industrial marvel for serious cleaning or concrete blasting. It effectively strips all types of marine fouling, corrosion and coatings to bare metal if needed.

#### Accessories Included:

Feed Hose (15 feet), By-Pass Hose (15 feet),  
High Pressure Hose (50 feet), Zero-Thrust Balanced Gun

#### Optional Accessories:

Additional pressure hose available in 50 ft or 100 ft sections  
Max. Pressure hose length recommended up to 300 ft (100 meters) total



SKID Dimensions	
Length	63" / 160 cm
Width	47" / 119 cm
Height	50" / 127 cm
Weight	2,500 Lbs / 1,136 kg
Lifting Eyes / FL Slots	YES / YES

Pump System	
Pressure Pump	HPP GLR 109/290
Pump Material Type	Coated Cast Iron / Triplex
Flow Rate	29 gpm / 110 Lpm
Nozzle Pressure	4,000 psi / 276 Bar
Hose Diam/Max Lgth	3/4" - 600 Lft

Feed System	
Feed Pump	Centrifugal Self-Priming
Lift	20 Lft / 6 meter
Flow Rate	62 gpm / 234 Lpm
Driver	Electric Motor

Drive System	
Driver	Electric Motor
Enclosure	TEFC
Frame	405T
Hertz	60 / 50
Voltage	230 / 460 Volts
Phase	3 Phase
Output	85 HP / 63 kW
Speed RPM	1,500 / 1,800 Rpm
Transmission	Direct Drive
Motor Control	Soft Start
Control Box	NEMA 4X / IP 56

Tools	
Tool Type	Zero-Thrust Balanced Gun

Shipping Dimensions	
Pallet 48x63x56"	2,650 Lbs Gross weight

\* Pricing and specifications subject to change without notice

CaviDyne LLC, 5077 Fruitville Rd. Suite - 109-157, Sarasota FL, 34232 USA

Phone: (352)275-5319, sales@cavidyne.com, www.cavidyne.com



# CAVIBLASTER™