

CaviBlaster 2570-D

Diesel Engine, 25 gpm & 7,000 psi

Specifications and Options

This is an industrial workhorse which generates a super stream of high velocity cavitation for high efficient cleaning, it can strip fouling, corrosion and coatings to bare metal if desired

Accessories Included:

Feed Hose (15 feet), By-Pass Hose (15 feet),
High Pressure Hose (50 feet), Zero-Thrust Balanced Gun, Battery Start

Optional Accessories:

Additional pressure hose available in 50 ft or 100 ft sections
Max. Pressure hose length recommended up to 300 ft (100 meters) total



SKID Dimensions	
Length	97" / 246 cm
Width	57" / 145 cm
Height	63" / 160 cm
Weight	5,000 Lbs / 2,273 kg
Fuel Containment Pan	YES
Lifting Eyes / FL Slots	YES / YES

Pump System	
Pressure Pump	Giant GP8135
Pump Material / Type	Positive Displacement
Flow Rate	25 gpm / 95 Lpm
Nozzle Pressure	7,250 psi / 500 Bar
Hose Diam/Max Lgth	3/4" - 600 ft - 19 mm / 200 m

Feed System	
Feed Pump	Centrifugal Self-Priming
Lift	20 ft / 6 meter
Flow Rate	40 gpm / 151 Lpm
Power Transm.	Belt Driven

Drive System	
Engine Tier-3	JCB
Engine Type	4-Cylinder / 4-Cycle
Cooling System	Liquid
Combustion System	Turbocharged
Max. Output	145 HP / 108 kW @ 2,200 rpm
Air Intake	TCA
Transmission	Belt Drive PTO
Starting System	Electric Starter
Emergency Shut-off	Electric

Tools	
Tool Type	Zero-Thrust Balanced Gun

Shipping Dimensions	
Pallet 58x98x70"	5,200 Lbs Gross weight

* Pricing and specifications subject to change without notice

CaviDyne LLC, 5077 Fruitville Rd. Suite - 109-157, Sarasota FL, 34232 USA

Phone: (352)275-5319, sales@cavidyne.com, www.cavidyne.com



caviBLASTER™